

A red, triangular badge pointing to the right, containing the word "New" in white, bold, sans-serif font.

New

A close-up photograph of a black, octagonal Duo Alarm device mounted on a grey control panel. The device has several ports and a small circular logo with the word "exma" inside. The background shows a blurred keypad and other panel elements.

Wireless surveillance of evacuation routes

Duo Alarm

A vertical decorative bar consisting of a blue segment on top and a yellow segment on the bottom.

The Swedish made locking system



Standalone monitoring of unauthorized passage

Safe and secure

Exma Duo Alarm offers flexible, passive passage control. The door is kept unlocked and if no valid code is entered prior to opening it, the alarm is triggered. An ideal solution in situations where e.g. escape routes are led via storerooms or other sensitive areas. The system holds up to 999 codes, with a length of 3-7 digits each.

Easy to install

The Exma Duo is a standalone solution, easy to install. No further wiring or perforation is required. Neither in the door itself, the frame nor the wall.

User friendly

The system is very convenient for the user. All features are directly available via the keypad on the device.

Duo Alarm specifications

Battery voltage. (4 pcs 1.5V AA standard batteries = 6V)	Yes
Standalone	Yes
System indications	Yes
Lock operation with door pressure	Yes
Acoustic verification	Yes
Battery life, normal use	12-24 months without alarms 12 h with alarms
Battery warning	Yes
Size, external unit, WxHxD	70x230x10 mm
Size, internal unit, WxHxD	80x300x28 mm
Alarm on in- and outside	Yes
Alarm volume	ca 100 dB

